

## Pegasus Part No. 3062 Alloy Steel Rod Ends (Aurora RAM and RAB Series)

These high-strength rod end bearings provide excellent strength, durability, and safety. The body and race are both alloy steels, heat-treated and nickel-plated. The ball is heat treated and hard chrome plated alloy steel, and the race has a self-lubricating PTFE fabric lining bonded to it. These bear-

ings are very resistant to loosening, even when subjected to the pounding they receive under racing conditions. Male threaded solid shanks only. Aurora RAM-T (right hand threads) and RAB-T (left hand threads) series.





**Body:** Alloy steel, heat treated, nickel or chrome plated for corrosion resistance.

**Race:** Alloy steel, heat treated, nickel plated for corrosion resistance.

**Ball:** Alloy steel, heat treated and hard chrome plated.

**Lubrication:** Self-lubricating PTFE liner.

Aurora RAM (Right Hand) / RAB (Left Hand) Alloy Steel Rod Ends, Male Threaded Shanks										
В		С	Α	W	Н	D	a°			
Bore	Thread (UNJF-3A)	Thread Length	Center of Bore to End of Shank	Ball Width	Head Thickness	Head Diameter	Misalignment Angle	Weight, Ounces (Approx.)	Static Radial Load	Pegasus Part No.
+.0015		+.062 031	±.010	+.000 005	±.005	+.000 020			Rating*	
1/4"	<sup>1</sup> ⁄ <sub>4</sub> -28	1″	1 <sup>9</sup> / <sub>16</sub> "	3/8"	9/32"	3/4"	16°	.7	5260 lb	3062-4-L or -R
<sup>5</sup> /16"	<sup>5</sup> / <sub>16</sub> -24	1 <sup>3</sup> / <sub>16</sub> "	1 1/8"	<sup>7</sup> / <sub>16</sub> "	11/32"	7/8"	14°	1.2	7125 lb	3062-5-L or -R
3/8"	<sup>3</sup> / <sub>8</sub> -24	1 <sup>3</sup> / <sub>16</sub> "	1 <sup>15</sup> / <sub>16</sub> "	1/2"	13/32"	1″	12°	1.8	8939 lb	3062-6-L or -R
7⁄ <sub>16</sub> "	<sup>7</sup> / <sub>16</sub> -20	1 <sup>5</sup> / <sub>16</sub> "	2 1/8"	<sup>9</sup> /16"	<sup>7</sup> / <sub>16</sub> "	1 ½"	14°	2.6	9653 lb	3062-7-L or -R
1/2"	<sup>1</sup> / <sub>2</sub> -20	1 ½16"	2 <sup>7</sup> / <sub>16</sub> "	5/8"	1/2"	1 <sup>5</sup> / <sub>16</sub> "	12°	4	15,500 lb	3062-8-L or -R
5/8"	<sup>5</sup> / <sub>8</sub> -18	1 <sup>9</sup> / <sub>16</sub> "	2 <sup>5</sup> /8"	3/4"	<sup>9</sup> /16"	1 1/2"	16°	6.1	17,148 lb	3062-10-L or -R
3/4"	<sup>3</sup> ⁄ <sub>4</sub> -16	1 <sup>11</sup> / <sub>16</sub> "	2 1/8"	7⁄ <sub>8</sub> "	<sup>11</sup> / <sub>16</sub> "	1 <sup>3</sup> ⁄ <sub>4</sub> "	14°	10	27,021 lb	3062-12-L or -R

<sup>\*</sup> Divide by 10 to calculate the axial load rating.

Part No. 3062 Alloy Steel Rod Ends, Male Shank

Aurora Rod End Bearings

Suspension Technical Documents

